



## Technical datasheet

### Jacmounts GLV 75 /716

For tool, plastic and textile machines, graphic and general production machines. Superior isolation and damping properties. Excellent non-skid properties.

Max. load  
**1800 lbs**

#### Article information

For tool, plastic and textile machines, graphic and general production machines. Superior isolation and damping properties. Excellent non-skid properties.

Type	GLV 75 /716
Name	Jacmounts
Art. no.	1.10075.56
Color	RAL 7001 silver grey
Other colors upon request.	
Surface treatment	painted

#### Technical Data

Max. load [lbs]	1800
Weight [kg]	0.42
Temperature range from [°C]	-15
Temperature range to [°C]	100


#### Dimensions

Height H [mm]	25
Height H <sub>min</sub> [mm] M12	37.5
Height H <sub>min</sub> [mm] M16	41
Length L [mm]	81
Width B [mm]	81

#### Pad equipment

Bottom pad type	716
Pad thickness unloaded [mm]	15
Coefficient of friction on concrete with fine mortar	0.85
Hardness [° Shore A]	70 - 75
Bottom pad area A <sub>1</sub> [cm <sup>2</sup> ]	50

#### Suitable studs, special studs, leveling screws, leveling sockets

	Studs S	M12, M16	<a href="#">more</a>
---	---------	----------	----------------------



#### Remark extent of supply

Studs need to be ordered separately.

#### Type illustration



Dimensioned sketch



#### Mounting sketch

