

A407OIL-P, A615OIL-P



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous
- Possibility of sucking and discharging the liquid at the same time (please refer to the pro-cedures as mentioned in the “use and maintenance” instructions)
- Sensor for the minimum level that cuts off the discharge of the liquid
- Electric cable 10m with industrial plug 3Ph+T 16A
- Oil mist filter Ø220mm
- Quick inlet Ø50mm
- 400lt and 600lt liquid collection container
- 60-litre swarf collection container with tilting hopper
- Mesh basket code 20214 already as standard
- Rear wheels in cast iron Ø200mm, front wheels Ø200mm with brake
- Version fully painted Ral 7001 grey
- Drain hose Ø30 (6 m. long) with manual ball valve to discharge the sucked liquids
- Double handle for better moving the vacuum cleaner
- Lifting set up for fork forklift
- Recommended use with Ø50mm sucking accessories (fitting for quick coupling 65229 already included)

		A407OIL-P	A615OIL-P
Tension/ Voltage	Volts	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 32A	3P + T 32A
Power	kW	5.5 + 0.55	12.5 (11+1.50)
Depression max	mbar max	450	500
Max working depression	mbar	360	430
Max air flow	m ³ /h	310	520
Liquids expulsion flow rate	lt/m	230	400
Container capacity for chips	lt	60	60
Container capacity for liquids	lt	400	600
Product inlet	mm	Ø50	Ø50
Noise level	DbA	75	76
Overall dimensions	cm	135x70x200h	150x75x215h
Weight	Kg	350	480
Protection	IP	55	55

* other voltages and frequencies available on request